

# SkidWeigh

ED2-EPT

Electric Pallet Truck On-board Check Weighing

## Automatic Freight Weight Verification for Electric Pallet Trucks

The **ED2-EPT Series SkidWeigh** system is general application, fully automatic microprocessor electronic device that measures the load weight on any type of electric pallet truck.

*The load weighing accuracy is within +/- 1% to 3% of the vehicle lifting capacity.*

Every time a skid load is picked up, the increase in hydraulic pressure on the vehicle will automatically activate the "weighing cycle at sample rate of 16000 readings per second" and convert it to a load weight measurement that is visually presented to the operator via a five digit LED display.



**Step 1.** Pick up the skid and read the load weight shown on the indicator.

**Step 2.** Compare the indicated load weight against the reported load weight.

- A. *If the load weight variance is within the acceptable company level, then the skid load can move to the destination trailer, holding area, etc.*
- B. *If the load weight variance is over the acceptable company level, then the skid load is moved to the "Legal for Trade" floor scale for final verification and creation of a scale ticket.*

### Review for Management

*Example: Freight Transportation Facilities*

Based on typical freight weight charges of \$10.00\* per 100 pounds and with a weight recovery program of only 1,000 pounds per forklift, per working day; your company revenue can increase approximately \$ 25,000 per operator, per year.

This equates to a return of ten times your investment cost for the first year. Payback can be as little as four weeks, depending on the shipping practices of your customers and your timing and approach to recouping these lost

### Benefits and ROI Analysis \*

Obviously the more forklifts equipped with on-board check weighing, the greater the potential return.

If it takes 10 forklifts to handle your cross dock volume and you have only one vehicle equipped with a SkidWeigh unit, you will be missing out on 90% of your potential freight weight recovery revenues.



Electronic Digital Indicator

## Installation

The ED2-EPT **Series SkidWeigh** System can be easily installed and calibrated by a local lift truck dealer technician or the end user's lift truck mechanic.

The installed system is calibrated automatically by lifting known load weight on the forks



Typical Installation of the ED2-EPT Series Pressure Transducer in Lifting Hydraulic Circuit



## Technical Data

### Electrical

- Voltage 12 to 55 V DC
- Current: Operating 80 mA

### Environmental

- Operating temperature  $-40^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$
- Water, dust and corrosion resistant, 4X protection

### Physical

- 120 x 80 x 55 mm, polycarbonate enclosure

### Technology

- Micro Controller

### Pressure Transducer

- Port connection, male thread 1/4"-18 NPT

- Proof pressure, 2.5 x range or 6,000 PSI
- Built-in pressure snubber
- Environmental: NEMA 4X
- Reverse polarity protection
- Over voltage protection
- Short circuit protection
- Housing material, Stainless steel, (AISI 303)
- Weight 95 grams
- Installation, unrestricted

### System Check Weighing Accuracy

+/-1% to 3% of pallet truck lifting capacity

### Mounting Bracket

- Adjustable mounting bracket included
- Anti-vibration mount, single ended

### LED Display Indicator

- Readout type, large six LED digits
- Readout range 50,000 kg or pounds
- Bright red display intensity
- Operating humidity range, 0-95% R.H.



Your Local Forklift Dealer